

SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: Låsespray

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricating oil

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier

ASSA ABLOY Opening Solutions Denmark A/S
Borupvang 5D
2750 Ballerup
info.dk.openingsolutions@assaabloy.com
www.assaabloy.dk

Telephone:

+45 4454 4454

Contact Person:

E-mail:

standard.dk.openingsolutions@assaabloy.com

1.4 Emergency telephone number:

Bispebjerg Hospitals giftlinje +45 82 12 12 12

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to regulation (EU) 1272/2008 (CLP).

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Aerosols

Category 1

H222: Extremely flammable aerosol.
H229: Pressurized container: May burst if heated.

Health Hazards

Aspiration Hazard

Category 1

H304: May be fatal if swallowed and enters airways.

Hazard summary

Physical Hazards:

Flammable aerosol.

Health Hazards

Product name: Låsespray

Skin Contact: At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Ingestion: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

2.2 Label Elements



Signal Words: Danger

Hazard Statement(s): H222: Extremely flammable aerosol.
H229: Pressurized container: May burst if heated.

Precautionary Statements

General information: P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.

Prevention: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.

Storage: P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Supplemental label information

EUH066: Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards: By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

General information: Mixture of components with propellant in aerosol can.

Chemical name	Identifier	Concentration *	REACH Registration No.	Notes
Propane	EINECS: 200-827-9	0% - <50,00%	01-2119486944-21	
Butane	EINECS: 203-448-7	0% - <50,00%	01-2119474691-32	
Isobutane (<0,1% 1,3-butadiene)	EINECS: 200-857-2	0% - <50,00%	01-2119485395-27	

Product name: Låsespray

Hydrocarbons, low viscosity	EINECS: 927-285-2	10,00% - <20,00%	01-2119480162-45	
Hydrocarbons, low viscosity	EINECS: 920-901-0	10,00% - <20,00%	01-2119456810-40	
Hydrocarbons, low viscous	EC: 918-167-1	10,00% - <20,00%	01-2119472146-39	

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Identifier	Classification
Propane	EINECS: 200-827-9	CLP: Flam. Gas 1A;H220, Press. Gas H280
Butane	EINECS: 203-448-7	CLP: Flam. Gas 1A;H220, Press. Gas H280
Isobutane (<0,1% 1,3-butadiene)	EINECS: 200-857-2	CLP: Flam. Gas 1A;H220, Press. Gas H280
Hydrocarbons, low viscosity	EINECS: 927-285-2	CLP: Asp. Tox. 1;H304
Hydrocarbons, low viscosity	EINECS: 920-901-0	CLP: Asp. Tox. 1;H304
Hydrocarbons, low viscous	EC: 918-167-1	CLP: Asp. Tox. 1;H304, Aquatic Chronic 4;H413

CLP: Regulation No. 1272/2008.

For the wording of the listed hazard statements refer to section 16.

SECTION 4: First aid measures

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids.

Skin Contact: Wash with soap and water.

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed: Dizziness Freeze burns If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. Dizziness Freeze burns

4.3 Indication of any immediate medical attention and special treatment needed May be fatal if swallowed and enters airways. Get medical attention if symptoms occur. Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: CO₂, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

Product name: Låsespray

Unsuitable extinguishing media: Water with a full water jet.

5.2 Special hazards arising from the substance or mixture: Danger of explosion with aerosol cans.

5.3 Advice for firefighters

Special fire fighting procedures: Use fire fighting measures that suit the environment. Move container from fire area if it can be done without risk. Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: Keep away from sources of ignition - No smoking.

6.2 Environmental Precautions: Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.

6.3 Methods and material for containment and cleaning up: Scrape up spillage or absorb with absorbing material. Stop the flow of material, if this is without risk. Dispose of the material collected according to regulations.

6.4 Reference to other sections: See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling: Avoid contact with flame and heat source, prevent contact with direct sunlight Use only in well-ventilated areas.

7.2 Conditions for safe storage, including any incompatibilities: Store locked up. Local regulations concerning handling and storage of waterpolluting products have to be followed. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Local regulations for the storage and handling of aerosol cans and flammable liquids have to be kept. Keep away from heat/sparks/hot surfaces. - No smoking.

7.3 Specific end use(s): Not applicable

Product name: Låsespray

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Chemical name	Type	Exposure Limit Values	Source
Propane	GV	1.000 ppm 1.800 mg/m ³	Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, An. 2 & 3, as amended (12 2011)
Butane	GV	500 ppm 1.200 mg/m ³	Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, An. 2 & 3, as amended (12 2011)

8.2 Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information:

Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

Eye/face protection:

Avoid contact with skin and eyes. Goggles/face shield are recommended. If risk of splashing, wear safety goggles or face shield.

Skin protection

Hand Protection:

Material: Nitrile butyl rubber (NBR).
Min. Breakthrough time: ≥ 480 min
Recommended thickness of the material: $\geq 0,38$ mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Other:

Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.

Respiratory Protection:

Do not breathe dust/fume/gas/mist/vapors/spray. Provide adequate ventilation. In case of inadequate ventilation wear respiratory protection. Filter AX/P2.

Product name: Låsespray

Thermal hazards:	No decomposition if used according to specifications.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.
Environmental Controls:	No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	Aerosols
Form:	Aerosols
Color:	Amber
Odor:	Slight
Odor Threshold:	Not applicable for mixtures
pH:	substance/mixture is non-soluble (in water)
Freezing point:	Not applicable for mixtures
Boiling Point:	175 °C
Flash Point:	< -60 °C (DIN EN ISO 2719)
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	Value not relevant for classification
Flammability Limit - Upper (%)—:	Value not relevant for classification
Flammability Limit - Lower (%)—:	Value not relevant for classification
Vapor pressure:	Not applicable for mixtures
Vapor density (air=1):	Not applicable for mixtures
Density:	0,80 g/cm ³ (15 °C) (DIN 51757)
Solubility(ies)	
Solubility in Water:	The product is insoluble in water.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Not applicable for mixtures
Autoignition Temperature:	Value not relevant for classification
Decomposition Temperature:	Value not relevant for classification
Kinematic viscosity:	3,5 mm ² /s (20 °C, DIN 51562)
Explosive properties:	Value not relevant for classification
Oxidizing properties:	Value not relevant for classification

9.2 Other information

Minimum ignition temperature:	265 °C (DIN 51794)
--------------------------------------	--------------------

Product name: Låsespray

SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal temperature conditions and recommended use. Stable under normal use conditions.
10.2 Chemical Stability:	Material is stable under normal conditions. Stable under normal use conditions.
10.3 Possibility of hazardous reactions:	None under normal conditions. Stable under normal use conditions.
10.4 Conditions to avoid:	Stable under normal use conditions.
10.5 Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.
10.6 Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral

Product:

Not classified for acute toxicity based on available data.

Specified substance(s)

Hydrocarbons, low viscosity

LD 50 (Rat): > 5.001 mg/kg (OECD 401)

Hydrocarbons, low viscosity

LD 50 (Rat): > 10.000 mg/kg

Hydrocarbons, low viscous

LD 50 (Rat): > 5.000 mg/kg (OECD 401)

Dermal

Product:

Not classified for acute toxicity based on available data.

Specified substance(s)

Hydrocarbons, low viscosity

LD 50 (Rabbit): > 5.001 mg/kg (OECD 402)

Hydrocarbons, low viscous

LD 50 (Rabbit): 3.160 mg/kg (OECD 402)

Product name: Låsespray

Inhalation

Product:

Not classified for acute toxicity based on available data.

Specified substance(s)

Butane

LC 50 (Rat, 4 h): 658 mg/l
Gas

Hydrocarbons, low viscosity

LC 50 (Rat, 4 h): > 5 mg/l

Skin Corrosion/Irritation:

Product:

Based on available data, the classification criteria are not met.

Serious Eye Damage/Eye Irritation:

Product:

Based on available data, the classification criteria are not met.

Respiratory or Skin Sensitization:

Product:

Skin sensitizer: Based on available data, the classification criteria are not met.
Respiratory sensitizer: Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Product:

Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product:

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product:

Based on available data, the classification criteria are not met.

Aspiration Hazard

Product:

May be fatal if swallowed and enters airways.

Other adverse effects:

No data available.

Product name: Låsespray

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity

Product: Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

Propane LC 50 (Fish, 96 h): > 1.000 mg/l

Isobutane (<0,1% 1,3-butadiene) LC 50 (Fish, 96 h): 28 mg/l

Hydrocarbons, low viscosity LC 50 (Fish, 96 h): > 1.000 mg/l

Hydrocarbons, low viscosity LC 50 (Fish, 96 h): > 101 mg/l

Hydrocarbons, low viscous LC 50 (Fish, 96 h): > 1.000 mg/l (OECD 203)

Aquatic Invertebrates

Specified substance(s)

Isobutane (<0,1% 1,3-butadiene) EC 50 (Water Flea, 48 h): 16,3 mg/l

Hydrocarbons, low viscosity EC 50 (Water Flea, 48 h): > 1.000 mg/l

Hydrocarbons, low viscous EC 50 (Water Flea, 48 h): > 1.000 mg/l (OECD 202)

Chronic ToxicityProduct: Based on available data, the classification criteria are not met.

Toxicity to Aquatic Plants

Specified substance(s)

Isobutane (<0,1% 1,3-butadiene) EC 50 (Alga, 72 h): 8,6 mg/l

Hydrocarbons, low viscosity EC 50 (Alga, 72 h): > 1.001 mg/l

Hydrocarbons, low viscous EC 50 (Alga, 72 h): > 1.000 mg/l (OECD 201)

12.2 Persistence and Degradability

Biodegradation

Product: Not applicable for mixtures

Product name: Låsespray

Specified substance(s)

Hydrocarbons, low viscosity

31 % (28 d, OECD 301F) Not readily degradable.

12.3 Bioaccumulative potential

Product:

Not applicable for mixtures

12.4 Mobility in soil:

Product:

Not applicable for mixtures

12.5 Results of PBT and vPvB assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects:

No data available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information:

Dispose in accordance with all applicable regulations.

Disposal methods:

Discharge, treatment, or disposal may be subject to national, state, or local laws.

European Waste Codes

16 05 04*: Gases in pressure containers (including halons) containing dangerous substances.

SECTION 14: Transport information

ADR/RID

- | | |
|------------------------------------|----------|
| 14.1 UN Number: | UN 1950 |
| 14.2 UN Proper Shipping Name: | AEROSOLS |
| 14.3 Transport Hazard Class(es) | |
| Class: | 2 |
| Label(s): | 2.1 |
| Hazard No. (ADR): | — |
| Tunnel restriction code: | (D) |
| 14.4 Packing Group: | — |
| 14.5 Environmental hazards: | — |
| 14.6 Special precautions for user: | — |

ADN

- | | |
|------------------------------------|---|
| 14.6 Special precautions for user: | — |
|------------------------------------|---|

Product name: Låsespray

IMDG

14.1 UN Number:	UN 1950
14.2 UN Proper Shipping Name:	AEROSOLS
14.3 Transport Hazard Class(es)	
Class:	2.1
Label(s):	2.1
EmS No.:	F-D, S-U
14.3 Packing Group:	—
14.5 Environmental hazards:	—
14.6 Special precautions for user:	—

IATA

14.1 UN Number:	UN 1950
14.2 Proper Shipping Name:	Aerosols, flammable
14.3 Transport Hazard Class(es):	
Class:	2.1
Label(s):	2.1
14.4 Packing Group:	—
14.5 Environmental hazards:	—
14.6 Special precautions for user:	—

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

Regulation (EC) No. 2037/2000 Substances that deplete the ozone layer: none

Regulation (EC) No. 850/2004 on persistent organic pollutants: none

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Vertical lines in the margin indicate an amendment.

Wording of the H-statements in section 2 and 3

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H413	May cause long lasting harmful effects to aquatic life.

Other information: The classification complies with the current EU lists; however, it has been supplemented with expert literature information and information provided



Product name: Låsespray

by/about our company. It was derived from the test data and/or the application of the conventional method.

Revision Date:

18.11.2020

Disclaimer:

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.