

## Signo readers

Models: 20, 20K, 40, 40K variants

Seos® and standard profile Signo readers

Experience a safer  
and more open world

Designed for maximum security, interoperability and convenience.

Futureproof security with inbuilt OSDP and totally remote management.

Easy Migration from Wiegand to OSDP.

A range of Signo models for all scenarios.

Mobile ready, slimline design.

Colour LEDs which can simply be changed.

Accepts wide range of credential technologies.

Bluetooth and Near Field Communication (NFC) compatibility.

Configure for read in or read in and out.

Contemporary, robust (IP65) design with inbuilt intelligent energy saving technology.



### Added versatility

Signo accepts a wide range of credential technologies – including Seos®, iCLASS, MIFARE®, Incedo mobile keys and ASSA ABLOY PULSE keys – as well as popular legacy credentials and proximity technologies. Your current and future credential support needs are covered.



### Superior quality

Signo readers are connected by design: They work out-of-the-box with mobile credential technologies including native Bluetooth and Near Field Communication (NFC). Migration from Wiegand to OSDP is simple, as is integration with an Incedo access control system.



### Flexible models

A choice of individual Signo models provides the flexibility you need to pick the right reader for every job. You can customize a Signo reader rollout to meet the exact needs of every door and opening at your site.

### Versions:



20



20K






40



40K



# Signo readers – Specifications

Reader series		Signo reader			
	ASSA ABLOY Signo Reader	<b>20</b> 	<b>20K</b> 	<b>40</b> 	<b>40K</b> 
<b>General Information</b>					
①	<b>Purpose</b>	Highly versatile platform designed to provide unmatched breadth of support for a wide range of verticals, including access control systems of the past, present and future			
	<b>Base Model &amp; Form Factors</b>	mullion	mullion keypad	wall switch	wall switch keypad
		See full list of product codes on next page			
	<b>Dimensions (width x length x depth)</b>	45 mm x 121.5 mm x 19.5 mm	45 mm x 121.5 mm x 21.5 mm	80 mm x 121.5 mm x 19.5 mm	80 mm x 121.5 mm x 21.5 mm
	<b>Product Weight</b>	Pigtail: 95 g Terminal: 75 g	Pigtail: 110 g Terminal: 90 g	Pigtail: 140 g Terminal: 120 g	Pigtail: 160 g Terminal: 140 g
	<b>Security Rating – Secure Element Hardware</b>	EAL 5+			
<b>Credential Technology Supported</b>					
📶	<b>2.4 GHz Credential compatibility</b>	Yes – Integrated, supports ASSA ABLOY Mobile Access			
	<b>13.56 MHz Credential compatibility</b>	Yes – Incedo credentials, both online and offline			
	<b>125 kHz Credential compatibility</b>	Yes – available in all standard profile			
		ASSA ABLOY Signo readers support for: HID proximity, Indala proximity, EM4102 proximity, AWID			
<b>Device Characteristics</b>					
⚡	<b>Mounting</b>	Mullion, single or double-gang switch box (EU)			
	<b>Connector Type</b>	Pigtail Cable – 0.5 m Terminal Block – flush mount*			
	<b>Color</b>	Black Bezel / Silver Trim / Black Trim available as an accessory			
	<b>Keypad</b>	Mullion – 2 x 6 capacitive / Wallswitch – 3 x 4 capacitive			
	<b>Material Housing</b>	Polycarbonate – UL94 V0 rated 12 VDC			
	<b>Operating Voltage Range</b>	12 VDC			
	<b>Current Draw (Max)</b>	250 mA			
	<b>Device Input &amp; Output</b>	Input: Tri-color LED, Buzzer, Hold Output: Tamper Relay			
	<b>Operating Temperature Range</b>	-35° C to +66° C 0% to 95% non-condensing			
	<b>Storage Temperature Range</b>	-40° C to +85° C			
<b>Device Features</b>					
📶	<b>Device Management</b>	HID Reader Manager, OSDP configuration			
<b>Device Characteristics</b>					
🌡️	<b>Environmental Rating</b>	UL294 Outdoor and Indoor rated			
	<b>Ingress Protection</b>	IP65			
	<b>Controller Communications</b>	OSDP or Wiegand, both integrated into base hardware			
<b>Device Features</b>					
⚠️	<b>Intelligent Power Mode</b>	Yes			
	<b>Velocity Attack Detection</b>	Yes			
	<b>Metal Environment Optimisation</b>	Yes – surface detection feature automatically calibrates read range			
<b>Certifications and Terms</b>					
✓	<b>Certifications</b>	RCM , CE (EU), Green circle certified			
	<b>Warranty</b>	Limited Lifetime			

\* available on special order

# Product code and model information for ordering ASSA ABLOY Signo Readers:



## ASSA ABLOY Signo Reader 20

- **RDR-2PSO**  
Signo 20 Seos Profile  
– OSDP
- **RDR-2PSW**  
Signo 20 Seos Profile  
– Wiegand
- **RDR-2PLO**  
Signo 20 Standard Profile  
– OSDP
- **RDR-2PLW**  
Signo 20 Standard Profile  
– Wiegand



## ASSA ABLOY Signo Keypad Reader 20K

- **RDR-2NSO**  
Signo 20K Seos Profile  
– OSDP
- **RDR-2NSW**  
Signo 20K Seos Profile  
– Wiegand
- **RDR-2NLO**  
Signo 20K Standard Profile  
– OSDP
- **RDR-2NLW**  
Signo 20K Standard Profile  
– Wiegand



## ASSA ABLOY Signo Reader 40

- **RDR-4PSO**  
Signo 40 Seos Profile  
– OSDP
- **RDR-4PSW**  
Signo 40 Seos Profile  
– Wiegand
- **RDR-4PLO**  
Signo 40 Standard Profile  
– OSDP
- **RDR-4PLW**  
Signo 40 Standard Profile  
– Wiegand



## ASSA ABLOY Signo Keypad Reader 40K

- **RDR-4NSO**  
Signo 40K Seos Profile  
– OSDP
- **RDR-4NSW**  
Signo 40K Seos Profile  
– Wiegand
- **RDR-4NLO**  
Signo 40K Standard Profile  
– OSDP
- **RDR-4NLW**  
Signo 40K Standard Profile  
– Wiegand

Communication type	NFC/ BLE	High Frequency								Low Frequency		
		Seos	iCLASS SE	iCLASS SR	iCLASS	MIFARE DESFire EV1/ EV2/EV3 (SIO)	MIFARE Classic (SIO)	MIFARE DESFire EV1/ EV2/EV3 (CSN)	MIFARE Classic (CSN)	125kHz HID Proximity	125kHz Indala Proximity	125kHz EM4102 Proximity
Credentials Technologies Supported	Seos (MobileIDs via NFC/BLE)	Seos	iCLASS SE	iCLASS SR	iCLASS	MIFARE DESFire EV1/ EV2/EV3 (SIO)	MIFARE Classic (SIO)	MIFARE DESFire EV1/ EV2/EV3 (CSN)	MIFARE Classic (CSN)	125kHz HID Proximity	125kHz Indala Proximity	125kHz EM4102 Proximity
Standard Profile	●	●	●	●	●	●	●	●	●	●	●	●
Seos Profile	●	●	—	—	—	—	—	—	—	—	—	—

**About ASSA ABLOY**

The ASSA ABLOY Group is the global leader in access solutions. Every day, we help billions of people experience a more open world.

ASSA ABLOY Opening Solutions leads the development within door openings and products for access solutions and homes, businesses and institutions. Our offering includes doors, door and window hardware, locks, access control and services.

**Australia:**

ASSA ABLOY Opening Solutions Australia  
235 Huntingdale Road  
Oakleigh, Victoria, 3166  
Australia  
1300 LOCK UP (1300 562 587)  
[assaabloy.com/au](http://assaabloy.com/au)

**New Zealand:**

ASSA ABLOY New Zealand Ltd  
6 Armstrong Road  
Albany, Auckland, 0632  
New Zealand  
[nzsales@assaabloy.com](mailto:nzsales@assaabloy.com)  
[assaabloy.com/nz](http://assaabloy.com/nz)