

5 Lever Mortice Deadlock

3G114

Application:

- For timber door hinged on the left or the right
- Keys are suitable for use on doors up to 50mm thick

Operation:

- Deadbolt is locked or unlocked by key from either side

Specification:

Reference	3G114
Case Size	67mm or 80mm
Backset	40mm or 53mm
Case	Silver powder coat
Forend	Stainless steel or brass
Box Strike Assembly	Painted to match forend
Deadbolt	Brass, with hardened steel rollers
Latch Bolt	na
Follower	na
Keying Groups	Standard differ or to pass (BP codes)
Keys supplied	Standard differ supplied with 2 keys. For locks to pass please specify number of keys required.
Key Blank Number	B-K722
Cut Key Number	B-5LC
NB	Not suitable for master keying
Rebate Kit	B-3G114R (13mm, 19mm and 25mm)

Features:

- Force resistant, anti drill, anti-pick and anti-saw security features
- Available with square forend and striking plate
- 14mm bolt throw
- Supplied with one plain escutcheon and one escutcheon with a cover plate, finished to match the faceplate/strike



Finishes:

- SC - Satin Chrome finish
- PL- Brass finish

Standards:



- EN1634-1 assessed for use on 60 minute timber fire doors

Ordering Code Example:

B-3G114-PL-67 (Boxed)

