

5 Detainer Deadlocking Latch 3R35 and 3R35X

Application:

- For timber door hinged on the left or the right where slam action is required
- Keys are suitable for use on doors up to 50mm thick
- Detainer style locks provide a higher number of key combinations than lever locks
- 3R35X is suitable for use on escape doors

Operation:

- When closed the door is secured by an automatic deadlocking action on the latch
- A hold back snib can be used to keep the latch in the withdrawn position
- Handles can be secured from both sides
- 3R35X, as the 3R35 but the inside handle cannot be locked allowing free egress at all times

Specification:

Reference	3R35 and 3R35X
Case Size	80mm
Backset	44mm
Centres	56mm
Case	silver powder coat
Forend	Stainless steel or brass
Box Strike Assembly	Painted to match forend
Latch Bolt	Sintered Iron
Follower	Sintered Iron
Keying Groups	Standard differ, to pass (BP 3R35 codes only) or masterkeyable to other detainer locks
Keys supplied	Standard differ supplied with 2 keys. For locks to pass or masterkeyed please specify the number of keys required
Key Blank Number	B-K521-S (Standard) B-K748 (RKS)
Cut Key Number	B-DET-STD (Standard Differ) B-DET-SK-1.500 (Servant Key) B-DET-MK-1.500 (Master Key)
NB	For use with handles ref 3R35F
Rebate Kit	B-3R35R (13mm, 19mm and 25mm, left or right handed)



Features:

- Force resistant and anti-pick security features
- Available with square forend and striking plate
- 10mm latchbolt throw
- 3R35 only can be supplied on patented RKS key section to prevent illicit copying

Finishes:

- SC - Satin Chrome finish
- PL- Brass finish

Standards:



- EN1634-1 assessed for use on 60 minute timber fire doors



Ordering Code Example:

Locks are handed, please state handing required when ordering
B-3R35-SC-80-LH
B-3R35X-PL-RH

