

INTERIOR FOLDING SYSTEMS

Section Index and General Guide

Select system for your interior folding door application.	Residential	Commercial	Industrial	Max. Door	Product	Data Sheet
APPLICATION	<u> </u>	Ö				
Residential						
For wardrobes				14kg	Bifold	D20
For room dividers				40kg	Husky 25 & 40	D30
Commercial						
For interior residential or commercial end folding partitions				65kg	Pacer Endfold	*
For interior residential or commercial centre folding partitions				65kg	Pacer Centrefold	*
For interior residential or commercial partitions. All doors equal width				75kg	Soltaire Pivotfold 45 & 75	D40
For interior residential or commercial end folding partitions				75kg	Soltaire Endfold 45 & 75	D50
For interior residential or commercial centre folding partitions				75kg	Soltaire Centrefold 45 & 75	D60
Industrial						
For interior industrial and commercial end folding partitions				35kg	Council 290 Endfold	*
For interior industrial and commercial end folding partitions				35kg	Council 290 Pivotfold	*
For interior industrial and commercial centre folding partitions				35kg	Council 290 Centrefold	*
For interior industrial and commercial end folding partitions				70kg	Council 301 Endfold	*
For interior industrial and commercial end folding partitions				70kg	Council 301 Pivotfold	*
For interior industrial and commercial centre folding partitions				70kg	Council 301 Centrefold	*
For interior industrial and commercial end folding partitions				80kg	Council 305 Endfold	*
For interior industrial and commercial centre folding partitions				80kg	Council 305 Centrefold	*
For interior industrial and commercial folding partitions. Bottom roll.				70kg	College Endfold	*
For interior industrial and commercial folding partitions. Bottom roll.				140kg	College Endfold	*

^{*} Please contact either your ASSA ABLOY Representative or our technical sales team for further information.



BIFOLD

For folding wardrobe doors. Max 14kg.

APPLICATION

- Stable and smooth opening system for wardrobe doors that can complement any bedroom
- System allows for doors to fold back completely
- Silent and easy to fix
- Designed for timber, timber framed or composite doors
- Suitable for jambless openings

DOOR SPECIFICATION

Track System
For Individual Doors:
Max Door Weight
Max Door Width
Door Thickness
Max Door Height
Door Height
Bifold
14kg
530mm
20-35mm
2400mm

STANDARD SETS AND PACK

Set No.

Sets comprise of track, top and bottom pivots, guides, hinges, all screws & fitting instructions.

Hardware for


HB10/2	1065mm	2 doors
HB15/4	1525mm	4 doors (2 doors to each side)
HB20/4	2135mm	4 doors (2 doors to each side)

Track Length


HARDWARE SPECIFICATION

Track	Н310	Aluminium (762, 1067, & 3000mm lengths)
Pivots	H311 H312 H312W H313 H314	Top pivot socket Bottom pivot socket Bottom pivot socket wall fix Top pivot Bottom pivot
	H289B	Bottom pivot set
Guide	Н315	Nylon spring loaded guide
Hinge	H282 H75X47FHSS H316 H319	Butt hinge Stainless steel face fix hinge Rubber buffer Door aligner











HUSKY 25 & 40

For folding doors and room dividers. Max 25kg or 40kg.

APPLICATION

- Ideally suited for light to medium weight residential folding partitions
- · Concealed fixing
- Suitable for timber, timber framed and composite doors

DOOR SPECIFICATION

Track System	Husky 25	Husky 40
For Individual Doors:		
Max Door Weight	25kg	40kg
Max Door Width	600mm	750mm
Door Thickness	20-40mm	20-40mm
Max Door Height	2400mm	2400mm

STANDARD SETS AND PACK


Sets comprise of steel track, hangers, top and bottom pivots, guides (*Husky 40*), hinges, all screws & fitting instructions.


Husky 25 Set No.	Husky 40 Set No.	Track Length	Hardware for
HF25/12 HF25/24	-	1200mm 2400mm	2 doors 4 doors (all 4 doors to one side)
-	HF40/15 HF40/30	1500mm 3000mm	2 doors 4 doors (all 4 doors to one side)
Pack No.		Application	
HF2/25 -	HF2/40	Two door fittings pack 25kg. Two door fittings pack 40kg.	
HF4/25 -	HF4/40	Four door, one end fittings pack 25kg. Four door, one end fittings pack 40kg.	

HARDWARE SPECIFICATION


Track	H280 H280A H280AN	Steel (2000, 3000, 4000 & 6000mm lengths) Aluminium (2000, 3000, 4000 & 6000mm lengths) Anodised (2000, 3000, 4000 & 6000mm lengths) Soffit fix spacing 275mm centres (maximum)
Pivots	H289T H289B	Top pivot Bottom pivot
Hangers (2 per door)	H283N H283	Nylon bodied, 4-wheel adjustable hangers (<i>Husky 25</i>) Nylon bodied, needle roller bearing hangers (<i>Husky 40</i>)
Hinge	H282HD H75X47FHSS H90X50FHSS	Husky butt hinge Stainless steel flush hinge Stainless steel flush hinge
Guides	H106/HF/94 H106SL/94	Roller guide Spring loaded guide
Channels	H81X H94X H94FM	Aluminium channel (1200, 1500, 1800, 2400 & 3600mm lengths) Aluminium (2000, 3000, 4000 & 6000mm lengths) Aluminium (2000, 3000, 4000 & 6000mm lengths)











SOLTAIRE PIVOTFOLD

For top hung interior pivot folding partitions. Max 75kg each leaf.

APPLICATION

- Manufactured from high grade 316 stainless steel with anodised aluminium track
- Suitable for residential and commercial pivot folding partition
- The folding unit is not hinged to the jamb, but is pivoted in the track and off the floor
- To cover any width of opening, any number of folding units can be used
- Folding units of up to eight leaves can be pivoted from a post
- Floating units can consist of four, six or eight leaves

DOOR SPECIFICATION

Track System	Soltaire 45	Soltaire 75
For Individual Door Leaves:		
Max Panel Weight	45kg	75kg
Max Panel Width	900mm	900mm
Panel Thickness	35-56mm	35-56mm
Max Panel Height	3000mm	3300mm

HARDWARE SPECIFICATION

Track System	Soltaire 45	Soltaire 75
Track	H180A	H250A

Anodised aluminium (2000, 3000, 4000 & 6000mm lengths)

Soffit fix spacing 900mm centres (maximum)

Brush Strips BS10, **BS15**, Available in black in 4 brush heights, by the metre

BS20, BS25 (mm)

Brackets H1/SS Face fixed stainless steel

Starting 20mm from end of track fix at 900mm maximum centres.

HangersH21/180/SSTimber doors 45kg 4 wheelH21/250/SSTimber doors 75kg 4 wheel

Pivots H21/SS/P Top and bottom pivot channel fix H21/SS/PNC Top and bottom pivots no channel

Track Stop HH5/SS Anodised aluminium with rubber buffer

Hinges HSF3S Non-mortice hinge handle set

(includes 2 hinges and 1 hinge handle)

HSF5S Non-mortice hinge set (includes 3 hinges)

H100X75LPSS Stainless steel butt hinge

H100X75DHSS Stainless steel D Handle butt hinge

Guides H21SS/94 Angle plate fixing stainless steel

Channels H94X Aluminium (2000, 3000, 4000 & 6000mm lengths)

H94 Brass (4000 & 6000mm lengths)

H89SS Stainless steel (2000 & 3000mm lengths)

H94P Polypropylene (2000, 3000, 4000 & 6000mm lengths) **H94PSC** Aluminium supporting channel and polypropylene


(2000, 3000, 4000 & 6000mm lengths)

Flushbolts H190S 190mm flushbolt non-locking

H190LS 190mm flushbolt locking
H450S 450mm flushbolt locking
H450LS 450mm flushbolt locking
H600S 600mm flushbolt non-locking
H600LS 600mm flushbolt locking


Flush Pulls

IMAGE COMING SOON



D40





SOLTAIRE ENDFOLD

For top hung interior end folding partitions. Max 75kg each leaf.

APPLICATION

- Manufactured from high grade 316 stainless steel with anodised aluminium track
- Suitable for residential and commercial centre folding partition
- Folding units up to 8 leaves can be hinged to a post
- To cover any width of opening, any number of folding units can be used

• Floating units can consist of four, six or eight leaves

DOOR SPECIFICATION

Track System For Individual Door Leaves:	Soltaire 45	Soltaire 75
Max Panel Weight	45kg	75kg
Max Panel Width	900mm	900mm
Panel Thickness	35-56mm	35-56mm
Max Panel Height	3000mm	3300mm

HARDWARE SPECIFICATION

Track System	Soltaire 45	Soltaire 75
Track	H180A	H250A

Anodised Aluminium (2000, 3000, 4000 & 6000mm lengths)

Soffit fix spacing 900mm centres (maximum)

Brush Strips BS10, BS15, Available in black in 4 brush heights, by the metre

BS20, BS25 (mm)

H1/250 **Brackets** Face fixed stainless steel

Starting 20mm from end of track fix at 900mm maximum centres.

H21/180/SS Hangers Timber doors 45kg 4 wheel H21/250/SS Timber doors 75kg 4 wheel

HH5/SS **Track Stop** Anodised aluminium with rubber buffer

Hinges HSF3S Non-mortice hinge handle set (includes 2 hinges and 1 hinge handle)

> HSF5S Non-mortice hinge set (includes 3 hinges)

H100X75LPSS Stainless steel butt hinge

H100X75DHSS Stainless steel D Handle butt hinge

Guides H21SS/94 Timber doors angle plate to suit 94 channel

Channels H94X Aluminium (2000, 3000, 4000 & 6000mm lengths)

> Brass (4000 & 6000mm lengths) H94

H89SS Stainless steel (2000 & 3000mm lengths) Н94Р Polypropylene (2000, 3000, 4000 & 6000mm lengths)

H94PSC Aluminium supporting channel and polypropylene


(2000, 3000, 4000 & 6000mm lengths)

Flushbolts H190S 190mm flushbolt non-locking


H190LS 190mm flushbolt locking H450S 450mm flushbolt non-locking H450LS 450mm flushbolt locking 600mm flushbolt non-locking H600S H600LS 600mm flushbolt locking

Flush Pulls

IMAGE COMING SOON







SOLTAIRE CENTREFOLD

For top hung interior Centre folding doors. 45kg & 75kg each leaf.

APPLICATION

- Manufactured from high grade 316 stainless steel with an anodised aluminium track
- Suitable for residential and commercial centre folding partition
- The leaves are hung centrally under the lintel and can fold to one or both sides
- Folding units of up to 7 full leaves and 1 half leaf can be hinged to a post
- Floating units consists of five, seven or nine full leaves
- To cover any width of opening, any number of folding units can be used

DOOR SPECIFICATION

Track System	Soltaire 45	Soltaire 75
For Individual Door Leaves:		
Max Panel Weight	45kg	75kg
Max Panel Width	900mm	900mm
Panel Thickness	35-56mm	35-56mm
Max Panel Height	3000mm	3300mm

HARDWARE SPECIFICATION

Track System	Soltaire 45	Soltaire 75
Track	H180A	H250A

Anodised aluminium (2000, 3000, 4000 & 6000mm lengths)

Soffit fix spacing 900mm centres (maximum)

Brush Strips BS10, **BS15**, Available in black in 4 brush heights, by the metre

BS20, BS25 (mm)

Brackets H1/SS Face fixed stainless steel

Starting 20mm from end of track fix at 900mm maximum centres.

Hangers H61/180/SS Timber doors 45kg **H61/250/SS** Timber doors 75kg

Pivots H21/SS/P Top and bottom pivot channel fix

H21/SS/PNC Top and bottom pivots no channel

Track Stop HH5/SS Anodised aluminium with rubber buffer **Hinges HSF3S** Non-mortice hinge handle set

(includes 2 hinges and 1 hinge handle)

Non mortischings set (includes 2 hings

HSF5S Non-mortice hinge set (includes 3 hinges)

H100X75LPSS Stainless steel butt hinge

H100X75D4SS Stainless steel D Handle butt hinge

Guides H106HSS/94 Concealed fixing stainless steel

Channels H94X Aluminium (2000, 3000, 4000 & 6000mm lengths)

H94 Brass (4000 & 6000mm lengths)

H89SS Stainless steel (2000 & 3000mm lengths)

H94P Polypropylene (2000, 3000, 4000 & 6000mm lengths) **H94PSC** Aluminium supporting channel and polypropylene

(2000, 3000, 4000 & 6000mm lengths)

Flushbolts H190S 190mm flushbolt non-locking

H190LS190mm flushbolt lockingH450S450mm flushbolt non-lockingH450LS450mm flushbolt lockingH600S600mm flushbolt non-locking

H600LS 600mm flushbolt locking

Flush Pulls

IMAGE COMING SOON

