



E7R-02135E91

ASSA ABLOY E7R-02135E91 fail safe electric strike

Features

- Fail safe (unlocked when power fail)
- It is suitable for wooden and aluminium door with not many daily passes
- Adjustable latch (max. 3mm)
- Due to 180° fitting, can be used DIN right and left
- Suitable for all access control systems with card

Technical Data

| | |
|------------------------|-------------------------|
| Break-in resistance | 300 kg |
| Operating type | Fail-safe |
| Height x Width x Depth | 75 mm x 20,5 mm x 28 mm |
| Voltage | 12V DC |
| Current Consumption | 245 mA @ 12V DC |
| Body | Zinc - aluminium alloy |
| Latch | Zinc - aluminium alloy |
| Faceplate | Stainless steel |
| Adjustable Latch Range | 3 mm |
| Monitoring | No |

ASSA ABLOY Kilitleme Sistemleri San. ve Tic. Ltd. Şti.
 İkitelli Org.San.Bölge. İpkaş San.Sit.
 3.Etap C Blok No:15 Başakşehir
 34490 İstanbul /Turkey

Tel : +90 212 503 41 00
 Fax : +90 212 552 52 55
 E-mail : proje@assaabloy.com

ASSA ABLOY
 Opening Solutions

Experience a safer
 and more open world